

## S5-GC(100-125)K-AU

# Solis Three Phase Grid-Tied Inverters

### Efficient

- 10 MPPTs, max. efficiency 99.0%
- > 150% DC/AC ratio
- High power tracking density 100MPPT/MW
- String current up to 16A, perfectly match large current bifacial modules

### Safe

- AFCI protection, proactively reduces fire risk
- Built-in PID recovery for better module performance (optional)
- Overvoltage load reduction and leakage current suppression technology, low failure rate
- Globally recognised branded componentry for longer life

### Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

### Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector

### Models:

S5-GC100K-AU

S5-GC110K-AU

S5-GC125K-HV-AU



## DATASHEET

## S5-GC(100-125)K-AU

Models	100K	110K	125K-HV
<b>Input DC</b>			
Max. input voltage		1100 V	
Rated voltage	600 V		720 V
Start-up voltage		195 V	
MPPT voltage range		180 - 1000 V	
Max. input current		10 × 32 A	
Max. short circuit current		10 × 40 A	
MPPT number / Max. input strings number		10 / 20	
<b>Output AC</b>			
Rated output power	100 kW	110 kW	125 kW
Rated apparent output power	100 kVA	110 kVA	125 kVA
Max. apparent output power	100 kVA	110 kVA	125 kVA
Max. output power	100 kW	110 kW	125 kW
Rated grid voltage	3/N/PE, 230 V / 400 V		3/PE, 480 V
Rated grid frequency		50 Hz	
Rated grid output current	144.3 A	158.8 A	150.4 A
Max. output current	144.3 A	158.8 A	150.4 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)		
THDi	< 3%		
<b>Efficiency</b>			
Max. efficiency	98.7%		99.0%
EU efficiency	98.3%		98.6%
<b>Protection</b>			
DC reverse-polarity protection		Yes	
Short circuit protection		Yes	
Output over current protection		Yes	
Surge protection	DC Type II / AC Type II (AC Type I optional)		
Grid monitoring		Yes	
Anti-islanding protection		Yes	
Temperature protection		Yes	
Strings monitoring		Yes	
I/V Curve scanning		Yes	
Integrated AFCI 2.0		Optional	
Integrated PID recovery		Optional	
Integrated DC switch		Yes	
Integrated AC switch		Optional	
<b>General Data</b>			
Dimensions (W × H × D)	1065 × 567 × 344.5 mm		
Weight	91 kg		
Topology	Transformerless		
Self-consumption (night)	< 2 W		
Operating ambient temperature range	-30 ~ +60°C		
Relative humidity	0 - 100%		
Ingress protection	IP66		
Cooling concept	Intelligent fan-cooling		
Max. operation altitude	4000 m		
Grid connection standard	AS/NZS 4777.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530		
Safety / EMC standard	IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4		
<b>Features</b>			
DC connection	MC4 connector		
AC connection	OT terminal (max. 185 mm <sup>2</sup> )		
Display	LCD		
Communication	RS485, Optional: Wi-Fi, GPRS, PLC		
Country of manufacture	China		